



BEST NEW ITEMS

NOVEMBER
2022

Knipex Twin-Grip Pliers #10887

The Twin-Grip Pliers from Knipex are a great option for gripping, tightening and loosening screws with worn heads and threads. They feature a unique combination of front and side grip functionality. It is constructed with a five-way slip joint with push button adjustment for precise modification of gripping capacity. The slim profile helps you work easily in confined spaces.

FEATURES:

- High-grip front jaw with robust teeth and high gear ratio
- Large front and side gripping capacity 5/32" to 7/8"
- Reliable front gripping of flat workpieces due to the three-point system
- Pinch stop reduces the risk of injury
- Forged from high-grade chrome vanadium electric steel, oil hardened.
- 8" Long



Everkem Fire Blocking Foam Sealant #60702

This is a ready-to-use polyurethane expanding foam for filling, insulating, and sealing the space around wires, vents, pipes, ducts, and other mechanical items that penetrate openings.

FEATURES:

- One 12 oz. can yield up to 15 tubes of caulk
- Tack free in as little as 10 minutes
- Able to be cut in as little as 1 hour
- Identifiable orange color
- Improves energy efficiency



Scan QR Code
for more
information



BEST FEATURED ITEMS

Did You Know Best Carries ...

Nebo Slyde Light

#10959



This 2-in-1 LED flashlight and work light generates 400 lumens and provides hours of continuous use. It features programmable memory settings for each light mode, a C•O•B* red light function with flashing red for emergency signaling, and a 4x adjustable zoom.

For work use, simply slide the light into its extended position to activate the LED work light and use the magnetic base to attach it to most metal surfaces for hands-free lighting. **pg. 10-54**

LIGHT MODES:

- Flashlight - Maximum (400 lumens) - 2 hours / 89 meters
- Flashlight - Minimum (40 lumens) - 20 hours / 28 meters
- Work Light - Maximum (400 lumens) - 3.5 hours / 32 meters
- Work Light - Minimum (40 lumens) - 25 hours / 10 meters
- Red - Maximum (40 lumens) - 2 hours / 9 meters
- Red - Minimum (4 lumens) - 8 hours / 4 meters
- Red Hazard Flasher (40 lumens) - 9 hours / 9 meters

FEATURES: Heavy duty aircraft-grade aluminum body
Water resistant | Impact resistant | Batteries included (4 AAA)

Winter Work Gloves

#10363 - L | #10367 - XL | 10370 - 2XL



These 15-gauge polyester knit shell gloves are great for outdoor work in harsh conditions. The gloves have a full latex coating with sandy grip coated palm and fingertips. They feature 7G terry lining for excellent warmth and comfort. **pg. 10-48**

FEATURES:

Full Latex Coated | Cut Resistant | Level A2 | Knit Wrist

Green Drain Waterless Trap Seal

#84015 - 2" | #84016 - 3" | #84017 - 3-1/2" | #84018 - 4"



Stop the spread of odor and pathogens through drains. Your facility can act like a vacuum, drawing air up through the foundation and openings like floor drains. Shut off toxic gases, odors, insects, and prevent minor flooding. These products can install in seconds and require no water to function properly. **pg. 8-27**

FEATURES:

- One-way valve creates seal to eliminate floor drain odor issues
- Sanitary, eco-friendly, and chemical-free solution
- Simple installation and improved drainage quality

Elkay Bottle Filling Station

#99610640

- No-Touch activated bottle filler
- Hermetically sealed refrigeration system provides chilled water.
- Fill rate is 1.1 GPM.
- Green Ticker™ informs user of number of 20 oz. plastic water bottles saved from waste.
- Laminar flow provides clean fill with minimal splash.
- ADA Compliant



YakTrax

#11233 - M (US Men's 9-11 / US Women's 10.5-12.5)
#11236 - L (US Men's 11.5-13.5 / US Women's 13-15)

- Spikeless traction device
 - Provides greater stability while walking on ice or snow
 - Prevents slips, falls, and injury
 - 360 degrees of traction with patented coil system
 - Made from thermoplastic rubbers for easy on/off
 - Outer band conforms to the length and width of your boot or shoe
- pg. 6-109**



Digital Pocket Thermometer

#91132

- Great for HVAC field service work
 - Ambient and direct contact readings
 - Range -40° to 572° F (-40° to 300° C)
 - Backlit display for visibility in low light
 - Max/Min, Hold and Average functions
 - 3-inch stainless steel probe
 - Removable protective sheath that doubles as a handle
- pg. 9-13**



DON'T FORGET BATTERIES!

pg. 10-53

